

# PIPING HOT

## NEW PRODUCTS

### Trap-Vent

- Approved Architectural Design Trap
- Choice of Satin or Polished Chrome
- Built in Studor Air Admittance Valve (requires no additional venting)
- Telescopic inlet fits 32 & 40 wastes with included adapters
- Outlet pipe with approved "key seal" connector and wall cover plate
- Comes apart for cleaning.
- Lifetime Guarantee



### The Best Thing Since Sliced Bread: FLOWSTOPPER™ plugging device

The FLOWSTOPPER™ plugging device is a new innovative Australian product designed by licensed plumber/inventor, Neal Borland. The smart plumbing tool makes obsolete traditional methods of plugging broken copper water pipes overcoming the common difficulty faced by plumbers in blocking the residual flow of water during the repair of broken copper water pipes when carrying out repairs (including the once popular, loaf of bread).



Following initial success in the Australian market FLOWSTOPPER Pty Ltd is now looking to expand distribution both domestically and internationally.

The FLOWSTOPPER™ plugging device was developed by Neal Borland – which he'd identified through his own maintenance plumbing business.

After ten years of extensive R&D and two years of field-testing, the FLOWSTOPPER™ plugging device has now been launched – providing a clever solution to a familiar problem faced by plumbers.

The product has been extremely well received by Australia's plumbing industry and is being picked-up by plumbers from around the country who have already discovered the benefits on offer including, quicker repair time and reduced costs.

The FLOWSTOPPER™ plugging device is now available at leading plumbing supply outlets throughout Australia including Reece.

### Nylex DownUnda Underground Rainwater Tank

CAPACITY: 5,000 litres  
 COLOUR: Black with alloy lid  
 DIMENSIONS: 3,500mm (l) x 2,800mm (w) x 800mm (h) (Max Riser height 400mm)  
 WEIGHT WHEN EMPTY: 400kg  
 MIN INSTALLATION DEPTH: 900mm  
 MAX INSTALLATION DEPTH: 1,200mm  
 TYPE: Polyethylene  
 LOAD BEARING CAPACITY: AS1170.2: 2,500kg max  
 10,000kg max option available



#### FEATURES:

- Safe to install - shallow excavation depth of 900mm means no need to work at depth
- Quick installation - can be installed in half a day
- Lightweight - only 400 kilograms
- Modular design allows tanks to be easily joined for additional storage
- Strong composite construction - designed and engineered for residential traffic
- Load vehicle traffic up to 2,500kg (10,000 kg option avail.)
- Strong alloy lid
- Child-resistant fasteners secure the lid; plus safety bars built-in to riser
- Flat pump recess in base allows for easy installation of a submersible pump
- 10 year warranty if installed to manufacturer's instructions

#### DESIGN STANDARDS:

AS 1170 Design Structures; AS4020; AS3600

### Space saving Rainwater Tanks from Freewater™

- Freewater™ tank modules are made from polyethylene plastic, stiffened and sleeved for strength and appearance.
- Each 1800x720x190mm module has the capacity to store approximately 220 litres of rainwater.
- The Freewater™ Modular Super - Slim Rainwater Tank attaches to a wall or may be positioned alongside a fence, and is held in place within a colour-matched, steel frame.
- With Freewater™ you can have your rainwater tank positioned in your driveway or walkway - it's the no-compromise water storage solution.
- 10 year guarantee under normal conditions.



For distributor details contact Freewater™ 0414 556 520