

DRAINCHEM

SEWER MAINTENANCE PRODUCTS



Example: 900-4854

- Doubles as a Grout Packer
- Comes with Test Panel
- 24" Wide Bladder
- Heavy Duty, Adjustable Wheels
- All Steel Construction
- Patented Telescopic Ports
- DuPont Kevlar® Reinforced Bladder
- Available in Higher Operating Pressures
- Successfully Tests T-Lock Pipe
- Several Inches of Clearance Between Bladder & Pipe Wall, Allowing Joint Tester to Negotiate bends in the Pipe & Clear Allowable Deflection
- Patent # 5066208



900 Series: Multi-Size Joint Testers / Grout Packers - High Pressure

PART #	SIZE RANGE	DIAMETER	WIDTH	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE TEST PRESSURE
900-2430	24.0"-30.0"	21.0"	24.0"	150 psi	100 psi
	610 mm-762 mm	533 mm	610 mm	10.3 bar	6.9 bar
900-3036	30.0"-36.0"	27.0"	24.0"	150 psi	100 psi
	762 mm-914 mm	686 mm	610 mm	10.3 bar	6.9 bar
900-3642	36.0"-42.0"	33.0"	24.0"	150 psi	100 psi
	914 mm-1067 mm	838 mm	610 mm	10.3 bar	6.9 bar
900-4248	42.0"-48.0"	39.0"	24.0"	150 psi	100 psi
	1067 mm-1219 mm	991 mm	610 mm	10.3 bar	6.9 bar
900-4854	48.0"-54.0"	45.0"	24.0"	150 psi	100 psi
	1219 mm-1372 mm	1143 mm	610 mm	10.3 bar	6.9 bar
900-5460	54.0"-60.0"	51.0"	24.0"	150 psi	100 psi
	1372 mm-1524 mm	1295 mm	610 mm	10.3 bar	6.9 bar
900-6066	60.0"-66.0"	57.0"	24.0"	150 psi	100 psi
	1524 mm-1676 mm	1448 mm	610 mm	10.3 bar	6.9 bar
900-6672	66.0"-72.0"	63.0"	24.0"	150 psi	100 psi
	1676 mm-1829 mm	1600 mm	610 mm	10.3 bar	6.9 bar
900-7278	72.0"-78.0"	69.0"	24.0"	150 psi	100 psi
	1829 mm-1981 mm	1753 mm	610 mm	10.3 bar	6.9 bar
900-7884	78.0"-84.0"	75.0"	24.0"	150 psi	100 psi
	1981 mm-2134 mm	1905 mm	610 mm	10.3 bar	6.9 bar
900-8490	84.0"-90.0"	81.0"	24.0"	150 psi	100 psi
	2134 mm-2286 mm	2057 mm	610 mm	10.3 bar	6.9 bar
900-9096	90.0"-96.0"	87.0"	24.0"	150 psi	100 psi
	2286 mm-2438 mm	2210 mm	610 mm	10.3 bar	6.9 bar
900-96102	96.0"-102.0"	93.0"	24.0"	150 psi	100 psi
	2438 mm-2591 mm	2362 mm	610 mm	10.3 bar	6.9 bar
900-102108	102.0"-108.0"	99.0"	24.0"	150 psi	100 psi
	2591 mm-2743 mm	2515 mm	610 mm	10.3 bar	6.9 bar

Custom Sizes Available!

**Always Read
Safety Information
Before Operation
Page 49**



Water or Air Test Panel
Part # 900-001



Testing

910 Series: Multi-Size Joint Testers / Grout Packers - Low Pressure



Example: 910-5460

- Doubles as a Grout Packer
- Comes with Test Panel
- 24" Wide Bladder
- Heavy Duty, Adjustable Wheels
- Patented Telescopic Ports
- DuPont Kevlar® Reinforced Bladder
- Successfully Tests T-Lock Pipe
- Several Inches of Clearance Between Bladder & Pipe Wall, Allowing Joint Tester to Negotiate bends in the Pipe & Clear Allowable Deflection

Available for Rent or Sale!

Our 910A Series Aluminum Joint Testers include all of the above features, plus:

- Lighter Weight
- No Rust - Easier to Clean Up
- Perfect for Rental



Example: 910A-4854

910 Series: Steel Multi-Size Joint Testers / Grout Packers - Low Pressure

PART #	SIZE RANGE	DIAMETER	WIDTH	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE TEST PRESSURE
910-2430	24.0"-30.0"	21.0"	24.0"	75 psi	25 psi
	610 mm-762 mm	533 mm	610 mm	5.2 bar	1.7 bar
910-3036	30.0"-36.0"	27.0"	24.0"	75 psi	25 psi
	762 mm-914 mm	686 mm	610 mm	5.2 bar	1.7 bar
910-3642	36.0"-42.0"	33.0"	24.0"	75 psi	25 psi
	914 mm-1067 mm	838 mm	610 mm	5.2 bar	1.7 bar
910-4248	42.0"-48.0"	39.0"	24.0"	75 psi	25 psi
	1067 mm-1219 mm	991 mm	610 mm	5.2 bar	1.7 bar
910-4854	48.0"-54.0"	45.0"	24.0"	75 psi	25 psi
	1219 mm-1372 mm	1143 mm	610 mm	5.2 bar	1.7 bar
910-5460	54.0"-60.0"	51.0"	24.0"	75 psi	25 psi
	1372 mm-1524 mm	1295 mm	610 mm	5.2 bar	1.7 bar
910-6066	60.0"-66.0"	57.0"	24.0"	75 psi	25 psi
	1524 mm-1676 mm	1448 mm	610 mm	5.2 bar	1.7 bar
910-6672	66.0"-72.0"	63.0"	24.0"	75 psi	25 psi
	1676 mm-1829 mm	1600 mm	610 mm	5.2 bar	1.7 bar
910-7278	72.0"-78.0"	69.0"	24.0"	75 psi	25 psi
	1829 mm-1981 mm	1753 mm	610 mm	5.2 bar	1.7 bar
910-7884	78.0"-84.0"	75.0"	24.0"	75 psi	25 psi
	1981 mm-2134 mm	1905 mm	610 mm	5.2 bar	1.7 bar
910-8490	84.0"-90.0"	81.0"	24.0"	75 psi	25 psi
	2134 mm-2286 mm	2057 mm	610 mm	5.2 bar	1.7 bar
910-9096	90.0"-96.0"	87.0"	24.0"	75 psi	25 psi
	2286 mm-2438 mm	2210 mm	610 mm	5.2 bar	1.7 bar
910-96102	96.0"-102.0"	93.0"	24.0"	75 psi	25 psi
	2438 mm-2591 mm	2362 mm	610 mm	5.2 bar	1.7 bar
910-102108	102.0"-108.0"	99.0"	24.0"	75 psi	25 psi
	2591 mm-2743 mm	2515 mm	610 mm	5.2 bar	1.7 bar

Custom Sizes Available!

910A Series: Aluminum Multi-Size Joint Testers / Grout Packers - Low Pressure

PART #	SIZE RANGE	DIAMETER	WIDTH	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE TEST PRESSURE
910A-2430	24.0"-30.0"	21.0"	24.0"	75 psi	25 psi
	610 mm-762 mm	533 mm	610 mm	5.2 bar	1.7 bar
910A-3036	30.0"-36.0"	27.0"	24.0"	75 psi	25 psi
	762 mm-914 mm	686 mm	610 mm	5.2 bar	1.7 bar
910A-3642	36.0"-42.0"	33.0"	24.0"	75 psi	25 psi
	914 mm-1067 mm	838 mm	610 mm	5.2 bar	1.7 bar
910A-4248	42.0"-48.0"	39.0"	24.0"	75 psi	25 psi
	1067 mm-1219 mm	991 mm	610 mm	5.2 bar	1.7 bar
910A-4854	48.0"-54.0"	45.0"	24.0"	75 psi	25 psi
	1219 mm-1372 mm	1143 mm	610 mm	5.2 bar	1.7 bar
910A-5460	54.0"-60.0"	51.0"	24.0"	75 psi	25 psi
	1372 mm-1524 mm	1295 mm	610 mm	5.2 bar	1.7 bar
910A-6066	60.0"-66.0"	57.0"	24.0"	75 psi	25 psi
	1524 mm-1676 mm	1448 mm	610 mm	5.2 bar	1.7 bar
910A-6672	66.0"-72.0"	63.0"	24.0"	75 psi	25 psi
	1676 mm-1829 mm	1600 mm	610 mm	5.2 bar	1.7 bar
910A-7278	72.0"-78.0"	69.0"	24.0"	75 psi	25 psi
	1829 mm-1981 mm	1753 mm	610 mm	5.2 bar	1.7 bar
910A-7884	78.0"-84.0"	75.0"	24.0"	75 psi	25 psi
	1981 mm-2134 mm	1905 mm	610 mm	5.2 bar	1.7 bar
910A-8490	84.0"-90.0"	81.0"	24.0"	75 psi	25 psi
	2134 mm-2286 mm	2057 mm	610 mm	5.2 bar	1.7 bar
910A-9096	90.0"-96.0"	87.0"	24.0"	75 psi	25 psi
	2286 mm-2438 mm	2210 mm	610 mm	5.2 bar	1.7 bar
910A-96102	96.0"-102.0"	93.0"	24.0"	75 psi	25 psi
	2438 mm-2591 mm	2362 mm	610 mm	5.2 bar	1.7 bar
910A-102108	102.0"-108.0"	99.0"	24.0"	75 psi	25 psi
	2591 mm-2743 mm	2515 mm	610 mm	5.2 bar	1.7 bar

Custom Sizes Available!

Patent # 5066208

Always Read Safety Information Before Operation Page 49



Water or Air Test Panel Part # 900-001



950 Series: Single-Size Joint Testers / Grout Packers - High Pressure



Example: 950-54

- Doubles as a Grout Packer
- Comes with Test Panel
- 18" Wide Bladder
- Heavy Duty, Adjustable Wheels
- All Steel Construction
- Patented Telescopic Ports
- DuPont Kevlar® Reinforced Bladder
- Available in Higher Operating Pressures
- Several Inches of Clearance Between Bladder & Pipe Wall, Allowing Joint Tester to Negotiate bends in the Pipe & Clear Allowable Deflection
- Successfully Tests T-Lock Pipe
- Patent # 5066208



950 Series: Single-Size Joint Testers / Grout Packers - High Pressure					
PART #	SIZE RANGE	DIAMETER	WIDTH	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE TEST PRESSURE
900-24	24.0"	21.0"	18.0"	150 psi	100 psi
	610 mm	533 mm	457 mm	10.3 bar	6.9 bar
900-27	27.0"	24.0"	18.0"	150 psi	100 psi
	686 mm	610 mm	457 mm	10.3 bar	6.9 bar
900-30	30.0"	27.0"	18.0"	150 psi	100 psi
	762 mm	686 mm	457 mm	10.3 bar	6.9 bar
900-33	33.0"	30.0"	18.0"	150 psi	100 psi
	838 mm	762 mm	457 mm	10.3 bar	6.9 bar
900-36	36.0"	33.0"	18.0"	150 psi	100 psi
	914 mm	838 mm	457 mm	10.3 bar	6.9 bar
900-39	39.0"	36.0"	18.0"	150 psi	100 psi
	991 mm	914 mm	457 mm	10.3 bar	6.9 bar
900-42	42.0"	39.0"	18.0"	150 psi	100 psi
	1067 mm	991 mm	457 mm	10.3 bar	6.9 bar
900-45	45.0"	42.0"	18.0"	150 psi	100 psi
	1143 mm	1067 mm	457 mm	10.3 bar	6.9 bar
900-48	48.0"	45.0"	18.0"	150 psi	100 psi
	1219 mm	1143 mm	457 mm	10.3 bar	6.9 bar
900-54	54.0"	51.0"	18.0"	150 psi	100 psi
	1372 mm	1295 mm	457 mm	10.3 bar	6.9 bar
900-60	60.0"	57.0"	18.0"	150 psi	100 psi
	1524 mm	1448 mm	457 mm	10.3 bar	6.9 bar
900-66	66.0"	63.0"	18.0"	150 psi	100 psi
	1676 mm	1600 mm	457 mm	10.3 bar	6.9 bar
900-72	72.0"	69.0"	18.0"	150 psi	100 psi
	1829 mm	1753 mm	457 mm	10.3 bar	6.9 bar
900-78	78.0"	75.0"	18.0"	150 psi	100 psi
	1981 mm	1905 mm	457 mm	10.3 bar	6.9 bar
900-84	84.0"	81.0"	18.0"	150 psi	100 psi
	2134 mm	2057 mm	457 mm	10.3 bar	6.9 bar
900-90	90.0"	87.0"	18.0"	150 psi	100 psi
	2286 mm	2210 mm	457 mm	10.3 bar	6.9 bar
900-96	96.0"	93.0"	18.0"	150 psi	100 psi
	2438 mm	2362 mm	457 mm	10.3 bar	6.9 bar

Custom Sizes Available!

Always Read
Safety Information
Before Operation
Page 49



Water or Air Test Panel
Part # 900-001



925 Series: Multi-Size Collapsible Joint Testers / Grout Packers - Low Pressure



Example: 925-3642
(collapsed)

- 30" Thru 60" Pipe
- Compatible with Today's Non-Standard Pipe I.D.'s
- Aluminum Construction
- Heavy Duty, Adjustable Wheels
- Comes with Air/Water Test Panel
- Patented Telescopic Ports
- Removable DuPont Kevlar® Reinforced Bladder
- No Grout Band to Remove
- Successfully Tests T-Lock Pipe
- 0-25 PSI Test Pressure
- Patent # 5066208



Example: 925-3642



The 18" wide bladder width and collapsibility allow for insertion down a 24" manhole. Simply remove wheels & pull 2 pins to collapse

Testing

925 Series: Multi-Size Collapsible Joint Testers / Grout Packers - Low Pressure					
PART #	SIZE RANGE	DIAMETER	WIDTH	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE TEST PRESSURE
925-3036	30.0"-36.0"	27.0"	18.0"	50 psi	25 psi
	762 mm-914 mm	686 mm	457 mm	3.5 bar	1.7 bar
925-3642	36.0"-42.0"	33.0"	18.0"	50 psi	25 psi
	914 mm-1067 mm	838 mm	457 mm	3.5 bar	1.7 bar
925-4248	42.0"-48.0"	39.0"	18.0"	50 psi	25 psi
	1067 mm-1219 mm	991 mm	457 mm	3.5 bar	1.7 bar
925-4854	48.0"-54.0"	45.0"	18.0"	50 psi	25 psi
	1219 mm-1372 mm	1143 mm	457 mm	3.5 bar	1.7 bar
925-5460	54.0"-60.0"	51.0"	18.0"	50 psi	25 psi
	1372 mm-1524 mm	1295 mm	457 mm	3.5 bar	1.7 bar

Custom Sizes Available!

**Always Read
Safety Information
Before Operation
Page 49**



Water or Air Test Panel
Part # 900-001

