

DRAINCHEM

SEWER MAINTENANCE PRODUCTS

"Distributed Exclusively in Australia by Drainchem"

PH301 - Sewer Jet 2500 PSI

APPLICATION

Standard Sewer cleaning vehicles and cleaning equipments.
 Special construction for optimum cut and wear resistance. Bonded tube and cover.
 Available in long lengths with a special cover, resistant to microbiological degradation.
 Lightweight compared to conventional rubber alternatives and increased lifetime.



APPLICABLE STANDARD

Polyhose proprietary product


CONSTRUCTION

Core: Thermoplastic Elastomer
 Reinforcement: 1 or 2 Braids of Synthetic Fiber
 Cover: Orange Color - Polyurethane

TEMPERATURE RANGE

-40°C to +60°C

Code	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		\$ Price
			(In)	(mm)	(In)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In)	
PH301-12	-12	20	3/4	19.2	1.150	29.2	2,500	175	6,250	438	125	5.0	
PH301-16	-16	25	1	25.5	1.450	36.8	2,500	175	6,250	438	160	6.4	
PH301-20	-20	32	1.1/4	32.0	1.800	45.7	2,500	175	6,250	438	250	10.0	



Polyhose

DRAINCHEM - CONTACT DETAILS

Email: office@drainchem.com.au

Web: www.drainchem.com.au

Ph: 03 5448 3795 Fax: 03 5448 3533

Mail Address: P.O. Box 5001

Sandhurst East Vic. 3550

A.B.N. : 50 645 068 573

PH302 - Sewer Jet 3000 PSI

Polyhose

APPLICATION

Standard Sewer cleaning vehicles and cleaning equipments.
 Special construction for optimum cut and wear resistance. Bonded tube and cover.
 Available in long lengths with a special cover, resistant to microbiological degradation.
 Lightweight compared to conventional rubber alternatives and increased lifetime.

APPLICABLE STANDARD

Polyhose proprietary product

CONSTRUCTION

Core: Thermoplastic Elastomer
 Reinforcement: 1 or 2 Braids of Synthetic Fibre plus one special extra braid
 Cover: Blue Color - Polyurethane

TEMPERATURE RANGE

-40°C to +60°C



Code	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		\$ Price
			(In)	(mm)	(In)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In)	
Part#			(In)	(mm)	(In)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In)	
PH302-20	-20	32	1. 1/4	32.0	1.840	46.7	3,000	210	7,500	525	250	10.0	

Crimp settings for poly hose +/- .1mm

3/16"	11.8mm	1/4"	15.4mm
3/8"	18.8mm	1/2"	25.0mm
3/4"	32.5mm	1"	40.1mm



PH303 - Sewer Jet 4000 PSI

APPLICATION

Standard Sewer cleaning vehicles and cleaning equipments.
 Special construction for optimum cut and wear resistance. Bonded tube and cover.
 Available in long lengths with a special cover, resistant to microbiological degradation.
 Lightweight compared to conventional rubber alternatives and increased lifetime.

APPLICABLE STANDARD

Polyhose proprietary product

CONSTRUCTION

Core: Thermoplastic Elastomer
 Reinforcement: 1 or 2 Braids of Synthetic Fiber / Aramid Fibre +1 special synthetic fiber braid
 Cover: Green Color - Polyurethane

TEMPERATURE RANGE

-40°C to +60°C



Code	Dash Size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		\$ Price
			(In)	(mm)	(In)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In)	
Part#			(In)	(mm)	(In)	(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)	(In)	
PH303-3	-3	5	3/16	4.8	0.405	10.3	4,000	280	12,000	840	40	1.6	
PH303-6	-5	10	3/8	9.6	0.670	17.0	4,000	280	12,000	840	75	3.0	
PH303-8	-8	12	1/2	12.8	0.920	23.4	4,000	280	12,000	840	75	3.0	



Web: www.drainchem.com.au
 Email: office@drainchem.com.au
 Ph: 03 5448 3795 Fax: 03 5448 3533

DRAINCHEM

SEWER MAINTENANCE PRODUCTS